



فرست اوتوماشن

Light Fittings

Series CZ0878d



Prodcuts Features

- It is long life and maintenance-free which the service life is up to 50000 hours and the maintenance-free of long term.
- There is a feature of good electromagnetic compatibility and it does not cause interference to the system power grid.
- It is not influenced by the voltage fluctuations and can be operated in the wide voltage range of 200 ~ 240V AC.
- There is a good performance of vibration due to the LED is the solid-state light source.
- There is a wide range of ambient temperature, which can be operated in the ambient temperature range of -40°C ~ +55°C.
- The degree of protection is up to Ip66.
- It is convenient to be mounted and maintained.
- International IECEx Approval, Europe union ATEX Approval.



فرست اوتوماشن

Light Fittings

Series CZ0878d



Product Parameter


| | |
|-----------------------------------|--|
| Product type: | Explosion-proof floodlight light fittings LED (wide beam, narrow beam, street light) |
| Certification: | CCC IECEX ATEX |
| Application range (zones): | 2G/Gb/zone 1; 2D/Db/zone 21 |
| Min.ambient temperature: | -20°C |
| Max.ambient temperature: | +55°C |
| Degree of protection: | IP66 |
| Rated voltage: | 110V~277V AC 50/60Hz |



فرست اوتوماشن



Light Fittings

Series CZ0878d



Bracket mounting

Pole mounting






فرست اوتوماشن

Light Fittings


Series CZ0878d



B—Bracket mounting



F—Pole mounting






فرست اوتوماشن

Light Fittings

Series CZ0878d




The diagram of the lamp pole



AH □



BH □



CH □



فرست اوتوماشن

Light Fittings

Series CZ0878d



Illustration

Order No.



B—Bracket mounting



F—Pole mounting

CZ0878d/□-LED120W-07-B-WB

CZ0878d/□-LED160W-07-B-WB

CZ0878d/□-LED200W-07-B-WB

CZ0878d/□-LED120W-07-B-NB

CZ0878d/□-LED160W-07-B-NB

CZ0878d/□-LED200W-07-B-NB

CZ0878d/□-LED120W-07-B-SL

CZ0878d/□-LED160W-07-B-SL

CZ0878d/□-LED200W-07-B-SL

Contact

info@first-automation.com.eg/ • 01101619222 – 01100200886 • <https://first-automation.com.eg/>



فرست اوتوماشن

Light Fittings

Series CZ0878d



Optional Ex components



| CZ0220 Series Plastic stopping plugs, the reducer



| CZ0221 Metal cable glands



| CZ0220 Series Plastic cable glands, stopping plugs



| CZ0226 Increased safety cable glands



| CZ0527, CZ1725/27 Increased safety breathing, drainage valve



| CZ0227 Increased safety metal cable glands



| CZ1725/1C Metal cable glands



| CZ1725/2A Metal cable glands



| CZ1725/3A Metal stopping plug



| CZ1725/1A Metal cable glands



| CZ1725/4A The reducer



| CZ1725/1B Metal cable glands



فرست اوتوماشن

Light Fittings

Series CZ0878d




Accessories



D623

Chain type accessories(500mm)

For M8 lifting eye bolt, the material is high quality steel with galvanization on surface



D8723/1

Bracket of vertical pole




فرست اوتوماشن

Light Fittings

Series CZ0878d



Accessories



AH,BH,CH

AH:Lamp pole of single arm
BH:Lamp pole of double arms with equal length
CH:Lamp pole of double arms with non-equal length



CZ0930

Code: 10,11
Single lamp equipped
with one fuse

code: 20,21
Double lamps equipped
with two fuses