



فرست اوتوماشن


Panel Mounting



Products Features

- The rated current of explosion-proof switches for panel mounting is up to 16A and the mechanical life is 1,000,000 times. There are silver or gold-plated silver contact points for options.
- Explosion-proof signal lamps for panel mounting have high brightness, long life. The electric life is more than 100,000 hours.
- Degree of protection IP66.
- IECEx International Certification, ATEX European Approval.

Product Parameter

Product type:	Explosion-proof module for panel mounting	
Certification:	CCC IECEx ATEX	
Application range (zones):	2G/Gb/zone 1; 2D/Db/zone 21	
Min.ambient temperature:	-40°C	
Max.ambient temperature:	+50°C	
Degree of protection:	IP66 (Match with operation head)	
Terminals:	2×2.5mm ²	
Cable entry:	Molded plastic 1×M20, cable outer diameter Φ5.5 ~ 13mm	



فرست اوتوماشن

Panel Mounting



CZ0201

Explosion-proof switch module
for panel mounting



CZ0212

Explosion-proof signal lamp with push
button module for panel mounting



Cz0202

Explosion-proof signal lamp module
for panel mounting



CZ0203

Explosion-proof potentiometer
module for panel mounting



فرست اوتوماشن

Panel Mounting



Illustration	Order No.	Illustration	Order No.	
 <p>CZ0201 Explosion-proof switch module for panel mounting</p>	CZ0201-90S	 <p>CZ0212 Explosion-proof signal lamp with push button module for panel mounting</p>	The voltage of signal lamp	
	CZ0201-90G		12V - 28V AC/DC	20V - 250V AC/DC
	CZ0201-91S		CZ0212-9303	CZ0212-9301
	CZ0201-91G		CZ0212-9403	CZ0212-9401
	CZ0201-92S			
	CZ0201-92G			
 <p>CZ0202 Explosion-proof signal lamp module for panel mounting</p>	CZ0202-903	 <p>CZ0203 Explosion-proof potentiometer module for panel mounting</p>	CZ0203-901	
	CZ0202-901		CZ0203-902	
			CZ0203-903	
CZ0202-902	CZ0203-904			
	CZ0203-905			
	CZ0203-906			
	CZ0203-907			
	CZ0203-908			
	CZ0203-909			
	CZ0203-910			
	CZ0203-911			
	CZ0203-912			
	CZ0203-913			
	CZ0203-914			